



ATHLO *belt*

Belt Hoist

For loads from 500 kg to 5.000 kg

ATHLO *belt* presents its advantages wherever cleanliness and safety are important. The numerous series features enable reliable and always safe operation. It can also be optimally adapted to individual requirements. In addition to the already available models with stainless steel components, further components in stainless steel will follow.

ATHLO *belt* is designed for the food sector, the chemical/pharmaceutical industry and for all comparable industries.



Minimal C-dimensions enable an optimal use of space

Powerful and durable hoist gear is configurable with different lubricants

The hoisting motor is contactor-controlled and enables two lifting speeds, 1/6

Control with proven strain relief

Limit switch with easily adjustable upper and lower limits

Manual, electric or curved trolleys (BH5 only) available. Optionally also available with fixed suspension

Reliable overload protection protects the hoist and the girder from overload

The support and deflection rollers ensure a perfect belt run even with a slight twisting or inclined pull

The belt is resistant to various acids, alkalis, mineral salts, solvents, and oil products

ATHLO belt

Belt Hoist

+ Optimal use of space

Minimal C-dimensions enable the optimal building design and the maximum use of the available working space.

+ Safety & Cleanliness

The high-tenacity and durable hoisting belt is ideal for applications in clean environments. The overload protection installed as standard prevents hoisting in the event of overload. Another protective device is the overheat protection, which is also installed as standard.

+ Extended offer

Numerous options such as corrosion protection version with stainless steel components, stainless steel hook, hook block and heat shield. Models with further loads will follow.



Size 2
2-, 3- or 4-fall models up to
2,000 kg



Size 5
2x2 or 2x4 up to
5,000 kg